

**WINMAN Elektrikli Aktüatörler WKKST Serisi/WINMAN Electric Actuators WKKST Series**



**Specification**

Specification	model Power Supply				
	WKKST-05B				
	DC24V	AC24V	AC110V	AC220V	AC380V
Power	13W	10W	10W	10W	6W
Rated Current	1.28A	1.50A	0.24A	0.16A	0.07A
Output Torque	50Nm		20Nm/50Nm		50Nm
90°Operational Time	30S		20S/30S		30S
Operational Angle Range	Adjustable from 0 to 360°				
Adapter Control Circuit	A/B/C/D/E/F/G/G1/BE				
Weight All	2.0kg				
Insulation Resistance	DC24V/AC24V:100MΩ/250VDC AC110V/AC220V/AC380V:100MΩ/500VDC				
Withstand Voltage	DC24V/AC24V:500VAC 1Minute, AC110V/AC220V:1500VAC 1Minute, AC380V:1800VAC 1Minute				
Enclosure Rating	IP65~IP68				
Mounting Direction	360° installed at any angle				
Electric Conduit	G1/2" waterproof cable connector				
Ambient Temperature	-30°C~+60°C				
Various Option	Fast turn-off, dehumidification heaters				

**Teknik Resim / Technical Drawing**

IS05211 connection	
Quartet	□9×9 □11×11 □14×14
Flange	F03 F05 F07
Stem	Height ≤ 19mm (or ≤ 32mm)

**WINMAN Elektrikli Aktüatörler WKKST Serisi / WINMAN Electric Actuators WKKST Series**



**Specification**

Specification	model WKKST-10B				
	DC24V	AC24V	AC110V	AC220V	AC380V
Power	25W	25W	25W	25W	15W
Rated Current	2.03A	2.12A	0.57A	0.30A	0.10A
Output Torque	100Nm			50Nm/100Nm	100Nm
90°Operational Time	30S			15S/30S	30S
Operational Angle Range	Adjustable from 0 to 360°				
Adapter Control Circuit	A/B/C/D/E/F/G/G1/BE				
Weight All	3.9kg				
Insulation Resistance	DC24V/AC24V:100MΩ/250VDC AC110V/AC220V/AC380V:100MΩ/500VDC				
Withstand Voltage	DC24V/AC24V:500VAC 1Minute, AC110V/AC220V:1500VAC 1Minute, AC380V:1800VAC 1Minute				
Enclosure Rating	IP65~IP68				
Mounting Direction	360° installed at any angle				
Electric Conduit	G1/2" waterproof cable connector				
Ambient Temperature	-30°C~+60°C				
Various Option	Fast turn-off, dehumidification heaters				

**Teknik Resim / Technical Drawing**

IS05211 connection		
Quartet	□9×9	□11×11 □14×14
Flange	F05	F07
Stem	Height ≤ 29mm	